



C65BP6-DSK | Eshalite Minimac

Bitumen emulsions for manufacturing thin surface course asphalt in cold mix application (DSK Asphalt)

Factory descriptor	Eshalite Minimac
Classes	5/15 10/20 15/25 20/30 25/35 30/40
Selection	We offer a selector tool to help you choose the proper class based on the expected ambient temperature range.
Application	For repairs to smaller areas that exhibit pavement damage or for the entire surface of bicycle paths or sidewalks. It is important to choose the right type of bitumen emulsion for proper paving results.
Properties	The Eshalite Minimac range is designed as a group of bitumen emulsions that can be applied with readily available aggregate within the specified temperature range. All classes comply with the requirements for bitumen emulsions for thin surface course asphalt in cold mix application in accordance with the valid TL BE-StB 15 standard (Technical Delivery Conditions for Bitumen Emulsions in Germany), which was harmonized with DIN EN 13808:2013 for the E.U. The specification laid down there establishes the grade designation, which provides a description of the main characteristics. Its use is mandatory. The suffix DSK complies with the national guidelines and specifies the exact purpose of the emulsion.
Handling	Manually or using small paving machinery
Packaging	Bulk in tank semi-trailers or other appropriate containers
Storage	Frozen-free storage in closed containers. Protect from exposure to sunlight. The Eshalite Minimac range is intended for immediate application after delivery.
Information	Please consult our website for further information at any time.

All information provided here is correct to the best of our knowledge in terms of development and application. It should not be understood as any guarantee of the suitability for particular applications, as it is only meant to provide information on our products. We reserve the right to make changes to this product specification sheet at any time.