



C60B4-N | Eshalite U60K-N

Bitumen emulsion for treating base courses with hydraulically bound mixtures

Factory descriptor	Eshalite U60K-N
Application	For treating base courses with hydraulically bound mixtures to provide a surface seal. It is important to choose the right type of bitumen emulsion for proper paving results.
Properties	Eshalite U60K-N is specially designed in terms of performance and breaking properties to seal hydraulically bound layers. It complies with the requirements for bitumen emulsions for hydraulically bound layers in accordance with the currently valid national TL BE-StB 15 standard (Technical Delivery Conditions for Bitumen Emulsions in Germany), which was harmonized with DIN EN 13808:2013 for the E.U. The specification laid down there establishes the grade designation, which provides a description of the main characteristics. Its use is mandatory. The suffix N complies with the national guidelines and specifies the exact purpose of the emulsion.
Handling	By machine equipped with special application machinery
Packaging	Bulk in tank semi-trailers or other appropriate containers
Storage	Frozen-free storage in closed containers. Protect from exposure to sunlight. Eshalite U60K-N is intended for immediate application upon delivery.
Information	Please consult our website for further information at any time.

All information provided here is correct to the best of our knowledge in terms of development and application. It should not be understood as any guarantee of the suitability for particular applications, as it is only meant to provide information on our products. We reserve the right to make changes to this product specification sheet at any time.