



Eshamac PM

Polymer-modified repair asphalt

| | |
|--------------------|---|
| Factory descriptor | Eshamac PM |
| Grading | 0/3 0/5 0/8 0/11 |
| Application | For quick and long-lasting repairs to horizontal asphalt layers, in particular for damage to the top coat and cracking in pavement on roads, sidewalks, or even parking lots. |
| Properties | <p>Eshamac PM is a cold, ready-mixed repair asphalt.</p> <p>We manufacture this product using a select, graded grain-size distribution and a specially developed polymer-modified bitumen emulsion. When properly applied, it can repair the damaged areas with a long-lasting effect.</p> |
| Handling | <p>It is important to choose the right grading based on the depth of the damage:</p> <p>Eshamac PM 0/3 <u>to up</u> 1 cm paving thickness – approx. 10–25 kg/m² of material necessary</p> <p>Eshamac PM 0/5 <u>to up</u> 2 cm paving thickness – approx. 20–40 kg/m² of material necessary</p> <p>Eshamac PM 0/8 <u>to up</u> 4 cm paving thickness – approx. 35–80 kg/m² of material necessary</p> <p>Eshamac PM 0/11 <u>to up</u> 6 cm paving thickness – approx. 75–115 kg/m² of material necessary</p> <p>After choosing the appropriate grading, and without applying joint tapes, the material is applied to a load-bearing surface, which has been sufficiently cleaned. Once the blend has been distributed throughout the damaged area, it must be compacted using a hand tamper, vibrating compactor, or light roller, depending on the surface area. Eshamac PM is ready for loading immediately after compacting.</p> |
| Packaging | 25 kg plastic bucket Disposable packaging bulk |
| Storage | plastic bucket Unopened buckets can be stored for up to twelve months. bulk Immediate use. Bulk products must be covered by a tarpaulin when in storage. |
| Information | Please consult our website for further information at any time. |

All information provided here is correct to the best of our knowledge in terms of development and application. It should not be understood as any guarantee of the suitability for particular applications, as it is only meant to provide information on our products. We reserve the right to make changes to this product specification sheet at any time.